



# TECHNICAL INFORMATION

Product dimensions LxWxH	610* x 325 x 610 mm
Tap height	345 mm
Voltage	230 V - 50 Hz
Max. load	2,55 A
Max. wattage	587 W
Volume drip tray	1000 cl
Possibility of connection to drain	Yes
Refrigerant gas	R-290 - 105g
Ambient temperature	10 - 32 °C
Weight	43 kg
OZONE	2 micrograms ozone per hour

Control	Touch
Display	10,1" touchscreen
Materials body	Inox 304 Safety glass 8 mm
Water pressure IN	2,5 - 4 bar
CO <sub>2</sub> pressure IN	4 bar
Temperature range OUT	4-12 °C
CAPACITY per hour	150 L*
Number of doses per water type	2
Taps to be operated simultaneously	Yes

\* Provide at least 50 mm additional space behind the device for installation.

\* With incoming water 14 °C

## Requirements

Electricity	1 x 230 V - 50Hz
Water connection	3/4" outlet valve with backflow prevention.
Extra space	Provide extra space around the device or in a cabinet close to the device for the filter and CO <sub>2</sub> bottle.

# AQUALEX

## HQ Belgium:

AQUALEX nv  
Nijverheidslaan 60/A  
8540 Deerlijk

T. +32 (0)56 96 70 00  
info@aqualex.eu  
www.aqualex.eu

## France:

AQUALEX  
10, Rue Michel Servet  
59000 Lille

T. +33 353 32 01 47  
info@aqualex.eu  
www.aqualex.eu/fr

All rights reserved.

The distribution and duplication of this document, as well as the use and disclosure of its contents are prohibited unless expressly authorised.  
This document is a translation of the original.